



## ” Modular 15" all-in-one POS system

### Specifications – P4100

- Slim POS system for those who value good looks
- Excellent performance thanks to Intel Celeron processor with 2.0 GHz
- Exchangeable interfaces for flexible requirements
- Available with resistive or capacitive touch
- IP64 water and dust proof front panel

		P4100
<b>System</b>	CPU	Intel Celeron J1900 QC 2.0 GHz
	System memory	4 GB SO-DIMM, DDR3L, 1333 MHz, max. 8 GB (1 bank)
	Chipset	Intel Baytrail platform
	Hard drive	120 GB SSD, HDD optional
	Supported OS	Windows 10 / Linux
<b>Housing</b>	Material	Aluminium
<b>Display</b>	Graphics chip	Intel HD graphics
	LCD size	38.1 cm (15") LCD
	Max. resolution	1024 x 768 pixels
	Brightness	350 nits, LED
	Touch screen	5-wire resistive, PCAP
	Tilt angle	0 to 90°
<b>Interfaces</b>	USB 2.0	3x (optional up to 6x)
	USB 3.0	1x
	Powered USB	1x (optional, 24 V)
	Serial / COM (RJ45)	4x (optional 5x) (powered 5 V / 12 V available)
	Parallel	Optional
	LAN	1x Gigabit
	VGA	1x
	Cash drawer port	1x (12 V / 24 V RJ11)
<b>PSU</b>	Power adapter	Integrated in the stand, 90 watts
<b>Other</b>	Dimensions (WxDxH)	374 x 265 x 339 mm
	Weight	Ca. 6.6 kg
	Operating temperature	0 to 35 °C
	Certification	CE, FCC, RoHS
<b>Options</b>	Mounting options	VESA 100 x 100 mm
	MSR	Yes
	Customer display	Yes (2 x 20 characters, integrated, pole)
	Customer-facing screen	Yes (8", 15", pole)
	Barcode scanner	Yes (1D, 2D)
	Waiter's lock	Yes (iButton)
	RFID	Yes (MiFare)
	Colour	Black, additional colours upon request
	UPS	Optional
	Interface options	In addition to the standard interfaces, the following options are available: <b>Option A</b> (2x USB, 1x UPS, 1x audio) <b>Option B*</b> (1x RS232, 1x UPS, 1x audio) <b>Option C</b> (2x USB, 1x 24 V pUSB, 1x audio) <b>Option D</b> (1x LPT)

Your partner

\*Only in combination with PCAP; factory fitted